



链号 Chain No.	E ₁ mm	E mm	F mm	W mm	H mm	H ₁ mm	H ₂ mm	H ₃ mm	d ₁ mm	d ₂ mm	d ₃ mm	型号 Type
C216AL-K2ZB-R	19.1	39	25.5	35.5	18	23	30	16.5	6.6	9.5	2.5	I
C216AL-K2ZB-L	19.1	39	25.5	35.5	18	21	25	11.5	6.6	12.5	9.3	II
C216AL-SK ₂ ·N ₁	19.05	39	28.18	38.73	19.05	-	31.75	17.2	6.6	9.5	-	I
C216AL-SK ₂ ·N ₂	19.05	39	28.18	38.73	19.05	22.05	26.05	11.5	6.6	12.5	9.3	II
C63.5S-R	25	47	25.5	36	24	29.5	36	16.5	6.6	9.5	2.5	I
C63.5S-L	25	47	25.5	36	24	27.5	31.5	12	6.6	12.5	9.3	II
C63.5S-N ₂	25	47	25.5	36	18	23.5	30	16.5	6.6	9.5	2.5	I
C63.5S-N ₁	25	47	25.5	36	18	21.5	25.5	12	6.6	12.5	9.3	II

链号 Chain No.	节距 Pitch P mm	内节内宽 Width between inner plates b ₁ (min) mm	滚子外径 Roller diameter D(max) mm	销 轴 Pin			链 板 Plate		最小抗 拉强度 Ultimate tensile strength Q(min) kN	型号 Type
				d mm	L ₁ mm	L ₂ mm	h mm	l/T mm		
C216AL-K2ZB-R	50.8	15.75	28.58	7.92	16.35	18.85	23.6	3	40	I
C216AL-K2ZB-L	50.8	15.75	28.58	7.92	16.35	18.85	23.6	3	40	II
C216AL-SK ₂ ·N ₁	50.8	15.75	28.58	7.92	16.35	18.85	23.6	3	40	I
C216AL-SK ₂ ·N ₂	50.8	15.75	28.58	7.92	16.35	18.85	23.6	3	40	II
C63.5S-R	63.5	15.75	39.68	7.92	16.35	18.85	23.5	3	40	I
C63.5S-L	63.5	15.75	39.68	7.92	16.35	18.85	23.5	3	40	II
C63.5S-N ₂	63.5	15.75	28.58	7.92	16.35	18.85	23.5	3	40	I
C63.5S-N ₁	63.5	15.75	28.58	7.92	16.35	18.85	23.5	3	40	II